

Heavy Duty Rubber Oil / Frac Delivery Hose (A451)

Application:	Used for oil, fuel, diesel and fracking applications.
Tube:	Black, smooth oil, diesel, fuel 50% aromatic and light chemical resistant
Reinforcement:	Textile high tensile
Cover:	Black, smooth heavy duty oil, weather ozone abrasion resistant rubber
Temperature:	-25°C to 70°C
Features:	• Minimum cut length of 5 mtrs, charges apply for cutting hose.

Part No.	Dimensions (mm)		Working Pressure		BP (PSI)	Bend Radius (mm)	Weight kg/mtr	Coil Lengths	Price \$ per mtr
	ID	OD	PSI	MPa					
A451100	101.6	124.0	400	2.75	1600	800	4.87	60	434.32

Price Group: HR
DB37



Rubber Petrol & Oil Bowser Hose (A420)

Application:	Used for fuel dispensing for regular & super grade petrol, unleaded petrol and diesel oil.
Tube:	Black, smooth, oil and petrol resistant, synthetic nitrile rubber
Reinforcement:	High tensile steel wire braid
Cover:	Black, smooth, oil, weather, ozone, abrasion and flame resistant synthetic rubber
Temperature:	-54°C to 85°C
Features:	• Minimum cut length of 5 mtrs, charges apply for cutting hose.
Standards:	UL Listed - MH45766

Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius	Weight kg/mtr	Price \$ per mtr
	ID	OD	PSI	MPa				
A420016	16.0	25.4	232	1.6	696	89	0.575	30.94
A420020	19.0	29.0	232	1.6	696	89	0.655	33.28
A420025	25.4	34.9	232	1.6	696	89	0.815	49.28

Price Group: HR
DB13

• Contact Dixon™ for coil lengths



Dubl-Grip® Reattachable Couplings for Pump Hose

Application:	Two piece re-attachable coupling made of chrome plated brass for pump hose. Worn portion of hose can be removed and Dubl-Grip® can be applied. Easy assembly - hose is held in position by sleeve as body is threaded home. Only a wrench is required to assemble the Dubl-Grip®. Caution - reattach static wire if required.
Design:	Streamlined design prevents damage to hose and fits smartly on new pump equipment. Wide, flat surfaces of body threads protect inside of hose from breaking. Tapered surfaces of sleeve and body cradle hose, prevent one-point strain from flexing. Hose is gripped on its full circumference in two places, ensuring a rigid leakproof connection.
Working Pressure:	300 PSI



Hose ID x NPT Male x Hose OD Size (inch)	Part No.	Price \$
5/8 x 3/4 x 1	850212	799.65
5/8 x 3/4 x 1-1/32	850213	137.45
5/8 x 3/4 x 1-1/16	850214	i 83.81
3/4 x 3/4 x 1-1/8	850451	92.16
3/4 x 3/4 x 1-13/64	850455	i 95.33
3/4 x 3/4 x 1-1/4	850453	i 32.47
1 x 1 x 1-3/8*	850841	141.01
1 x 1 x 1-7/16*	850801	190.03
1 x 1 x 1-1/2*	850811	181.74

Price Group: SD
AU05

Couplings have standard male NPT threads.

* Octagonal shape

Complete hose data specification sheets are available upon request.

