

## Dixon™ Worm Gear Clamps

<b>Features:</b>	<ul style="list-style-type: none"> <li>• clamp meets SAEJ1508 which supercedes Mil Spec WW-C-440B</li> <li>• four-piece construction</li> <li>• screw design: 8mm slotted hex head</li> <li>• maximum recommended torque 50 in. lbs.</li> <li>• <b>all clamps sold 10 per box</b></li> </ul>
<b>Materials:</b>	<p>Style HS material:</p> <ul style="list-style-type: none"> <li>• band and housing: SAE 300 series stainless</li> <li>• screw: SAE 1018 case-hardened, hex-free chrome zinc-plated steel</li> </ul> <p>Style HSS material:</p> <ul style="list-style-type: none"> <li>• band and housing: SAE 300 series stainless</li> <li>• screw: SAE 300 series stainless</li> </ul>

Hose OD Range (mm)		Box Qty	Style HS Clamps		Style HSS Clamps	
From:	To:		Part No.	Price \$ per box*	Part No.	Price \$ per box*
<b>12.7mm (1/2") Band Width</b>						
11	20	10	HS6	13.51	HSS6	16.67
12	23	10	HS8	12.74	HSS8	16.51
14	27	10	HS10	13.11	HSS10	16.92
17	32	10	HS12	12.70	HSS12	17.00
21	38	10	HS16	13.15	HSS16	16.94
21	45	10	HS20	13.80	HSS20	16.37
27	51	10	HS24	10.37	HSS24	17.08
33	57	10	HS28	17.82	HSS28	17.49
40	64	10	HS32	13.30	HSS32	17.62
46	70	10	HS36	13.77	HSS36	18.21
52	76	10	HS40	18.66	HSS40	19.83
59	83	10	HS44	20.74	HSS44	26.91
65	90	10	HS48	21.65	HSS48	23.74
71	95	10	HS52	22.64	HSS52	24.84
78	102	10	HS56	22.64	HSS56	25.42
84	108	10	HS60	23.27	HSS60	26.67
<b>14.3mm (9/16") Band Width</b>						
91	114	10	HS64	29.22	HSS64	27.46
48	127	10	HS72	27.36	HSS72	28.19
64	140	10	HS80	28.60	HSS80	28.66
79	152	10	HS88	29.30	HSS88	33.27
92	165	10	HS96	30.77	HSS96	32.04
105	178	10	HS104	30.44	HSS104	33.75
143	216	10	HS128	41.42	HSS128	52.08
181	254	10	HS152	47.25	HSS152	59.27
238	311	10	HS188	49.53	HSS188	65.57
257	330	10	HS200	51.85	HSS200	64.39
276	350	10	HS212	55.51	HSS212	68.08
295	368	10	HS224	61.55	HSS224	80.24
315	387	10	HS236	66.83	HSS236	80.01
334	406	10	HS248	70.21	HSS248	89.39
435	508	10	HS312	93.83	HSS312	101.88




Price Group: SD

Price Group: SD

AO02

AO03

 Maximum recommended torque 30 in./lbs.  
Torque ratings given on this page correspond to the torque rating of the screw of the clamp, and are not an indication of the working pressure of any hose assembly installed with this clamp.

