

Air King™ Double Bolt Clamps



Features:

- Torque values for clamps are based on dry bolts. The use of lubricant on bolts will adversely effect clamp performance.
- for use with Air King™ ends

Plated Iron					
Hose ID Size (inch)	Hose OD Range (inch)		Torque (ft lbs)	Part No.	Price \$ (ea)
	From:	To:			
½	25.4	30.2	6	A4	12.96
¾	28.6	33.3	12	A9	15.65
1	33.3	38.1	12	A10 ^{1,2}	18.55
1	38.1	46.0	21	A14	25.70

¹ can be used with **AM6** and **AM11**
² global investment cast carbon steel

Price Group: SD
AD04

E

Dixon™ Double Bolt Clamps



Features:

- inner surface has dual gripping ridges
- bolt lugs are reinforced to prevent bending out of alignment
- Torque values for clamps are based on dry bolts.
- The use of lubricant on bolts will adversely effect clamp performance.
- measure hose OD accurately before ordering clamps
- Consult Dixon® when using double bolt clamps on helical wire hose.

Hose OD (mm)		Torque (ft lbs)	Part No.	Price \$ (ea)
From:	To:			
Double Bolt Clamp Without Saddles				
28.6	30.2	15	J48	9.89
30.2	34.9	21	J49	16.08
36.5	38.9	21	JX49	15.62
41.3	46.0	40	DL14	22.59
44.5	52.0	27	DL20	21.63
53.6	58.3	27	DL24 ¹	17.42
58.7	66.7	40	DL32 ¹	21.76
63.5	69.9	40	DL275	28.71
69.9	77.8	60	DL306	34.38
77.8	85.7	60	DL328	38.06
82.6	88.9	60	DL350	36.57
Double Bolt Clamp With 2 Saddles				
88.9	96.8	40	400	36.36
96.0	103.2	40	431	41.31
102.4	108.7	40	463	33.39
108.0	125.4	60	525	42.50
114.3	133.4	60	550	41.49
130.2	144.5	60	600	54.64
144.5	150.8	60	639	99.20
150.8	165.1	60	675	53.81
165.1	192.1	60	769	62.88
195.3	208.0	125	818	93.43
209.6	225.4	125	875	88.03
227.0	250.8	125	988	106.28
252.4	288.9	125	1125	152.67
284.2	330.2	125	1275	347.02
309.6	355.6	200	1360	313.90
335.0	381.0	200	1450	395.58
382.6	444.5	260	1700	422.90

¹ Investment carbon steel

Price Group: SD
AD02



- Consult Dixon™ when using double bolt clamps on helical wire hose.
- NOTE: Measure Hose OD accurately before ordering Clamps

