


Dry Break Cam & Groove Dry Disconnect Couplings - Couplers ¹

Application:	Fully interchangeable with Kamvalok (OPW trademark) style fittings
Design:	Dixon™ EZ Boss-Lock™ cam arms standard on all 1½" and 2" fittings provide high security from accidental opening due to vibration or snagging. Large paddle type locking cam arms standard on 3" fittings, allow for an easy grip. Dry disconnect coupler has automatic closing poppet assembly. Strong handle attachment prevents bending of crank assembly
Materials:	<ul style="list-style-type: none"> • Heavy duty stainless steel crank and link • Stainless steel investment cast handles • Aluminium fittings have stainless steel ³ internals

Female NPT (inch)	Coupler Size (inch)	Seal Material	Part No.	Price \$
Aluminium				
1½	2	Buna	DBC61-150	1285.69
2	2½	Buna	DBC61-200	1276.68
3	4	Buna	DBC61-300	2322.56
1½	2	FKM	DBC62-150	886.97
2	2½	FKM	DBC62-200	1231.12
3	4	FKM	DBC62-300	2129.58
1½	2	PTFE Encapsulated Silicone and FFPM	DBC63-150	3265.92
2	2½	PTFE Encapsulated Silicone and FFPM	DBC63-200	3816.89
3	4	PTFE Encapsulated Silicone and FFPM	DBC63-300	5188.92
1½	2	EPT	DBC64-150	1955.47
2	2½	EPT	DBC64-200	2193.26
3	4	EPT	DBC64-300	3096.81
2	2½	FFPM and PTFE ²	DBC66-200	9240.19
3	4	FKMB	DBC69-300	3231.59
Stainless Steel ³				
1½	2	Buna	DBC71-150	2838.22
2	2½	Buna	DBC71-200	3189.23
3	4	Buna	DBC71-300	5925.55
1½	2	FKM	DBC72-150	2359.73
2	2½	FKM	DBC72-200	2982.51
3	4	FKM	DBC72-300	6697.68
1½	2	PTFE Encapsulated Silicone and FFPM	DBC73-150	4442.68
2	2½	PTFE Encapsulated Silicone and FFPM	DBC73-200	3075.31
3	4	PTFE Encapsulated Silicone and FFPM	DBC73-300	8933.52
1½	2	EPT	DBC74-150	2999.78
2	2½	EPT	DBC74-200	3181.26
3	4	EPT	DBC74-300	6424.58
1½	2	FFPM and PTFE ²	DBC76-150	10175.94
2	2½	FFPM and PTFE ²	DBC76-200	11236.92
3	4	FFPM and PTFE ²	DBC76-300	20393.59
1½	2	PTFE Encapsulated FKM and FFPM	DBC77-150	4534.19
2	2½	PTFE Encapsulated FKM and FFPM	DBC77-200	4305.90
3	4	PTFE Encapsulated FKM and FFPM	DBC77-300	8104.93
3	4	FKMB	DBC79-300	7070.07




1½" & 2" Coupler x Female NPT



3" Coupler x Female NPT

- ¹ A DBA style adaptor is required for coupler to operate. Adaptor sold separately.
- ² FFPM gasket, main seal O-ring and handle O-ring. PTFE seals on cylinder assembly, stuffing box, and seal under poppet screw.
- ³ Stainless steel corrosion resistance is equivalent to 304 stainless steel.



Greaseless Coupler x Female NPT (Stainless Steel)

Female NPT (inch)	Coupler Size (inch)	Seal Material	Part No.	Price \$
1½	2	PTFE Encapsulated FKM and FFPM	DBC77-150-GL	4871.60
2	2½	PTFE Encapsulated FKM and FFPM	DBC77-200-GL	5112.44

Coupler x 90° Swivel Female NPT (Aluminium)

Female NPT (inch)	Coupler Size (inch)	Seal Material	Part No.	Price \$
2	2½	Buna	DBS61-200	1439.35
2	2½	FKM	DBS62-200	1669.37
2	2½	PTFE Encapsulated Silicone and FFPM	DBS63-200	3568.74

Price Group: SD
AS02

Dust Plugs for Couplers



Size (inch)	Aluminum Part No.	Price \$	Stainless Steel Part No.	Price \$
2	ALDC200DP	10.65	SS200DP	42.88
2½	ALDC250DP	14.85	SS250DP	89.74
4	ALDC400DP	28.19	SS400DP	115.27

Price Group: CG
AL12, AS05

Locking Kit for Couplers



Description	Material	Part No.	Price \$
For use with 1½" & 2" dry disconnect couplers	Aluminium	DBCL-200	290.56
For use with 3" dry disconnect couplers	Aluminium	DBCL-300	288.12

Price Group: SD
AS02

