

Ribbed and Plain Dies

D



P29



R28

Ferrule ID	Std Ind Part #	Bore/Crimp Diameter ¹	Ribbed Die	Price \$	Plain Die	Price \$
.478"	4750	0.450	R41	284.50	P42	347.16
.500"	7322	0.475	R40	284.50	P40	347.16
.528"	7323	0.500	R39	284.50	P39	347.16
.528"	7324	0.500	R39	284.50	P39	347.16
.562"	7325	0.525	R37	284.50	P38	347.16
.593"	7326	0.550	R36	284.50	P37	347.16
.625"	7327	0.575	R35	284.50	P36	347.16
.656"	7328	0.600	R34	284.50	P35	347.16
.687"	7329	0.625	R33	284.50	P34	347.16
.718"	7330	0.675	R31	284.50	P32	347.16
.718"	7330B	0.675	R31	284.50	P32	347.16
.750"	7331	0.700	R30	284.50	P31	347.16
.750"	7331B	0.700	R30	284.50	P31	347.16
.781"	7332	0.725	R29	284.50	P30	347.16
.781"	7332B	0.725	R29	284.50	P30	347.16
.812"	7333	0.750	R28	284.50	P29	284.50
.380"	622	0.350	R44	284.50	P45	347.16
.400"	619	0.375	R44	284.50	P44	347.16
.410"	620	0.375	R43	284.50	P44	347.16
.450"	769	0.425	R41	284.50	P42	347.16
.500"	624	0.450	R40	284.50	P41	347.16
.525"	625	0.475	R39	284.50	P40	347.16
.548"	626	0.500	R38	284.50	P39	347.16
.564"	3588	0.525	R37	284.50	P38	347.16
.575"	KK	0.525	R37	284.50	P38	347.16
.600"	JJ	0.550	R36	284.50	P37	347.16
.625"	II	0.575	R35	284.50	P36	347.16
.650"	HH	0.600	R34	284.50	P35	347.16
.675"	GG	0.625	R34	284.50	P34	347.16
.725"	EE	0.675	R31	284.50	P32	347.16
.750"	DD	0.675	R30	284.50	P32	347.16
.775"	CC	0.700	R31	284.50	P31	347.16
.800"	---	0.750	R28	284.50	P29	284.50
.825"	---	0.775	R27	284.50	P28	284.50
.850"	Z	0.800	R26	284.50	P27	347.16
.875"	7244A	0.825	R25	284.50	P26	347.16
.900"	5029A	0.850	R24	284.50	P25	347.16
.937"	7242A	0.875	R23	284.50	P24	347.16
.975"	5028A	0.925	R21	284.50	P22	347.16
1.025"	7114A	0.975	R19	284.50	P20	347.16
1.175"	7088A	1.125	R13	284.50	P14	347.16
1.050"	3605	1.000	R18	284.50	P19	347.16
1.100"	5027A	1.050	R16	284.50	P17	347.16
1.150"	7104A	1.100	R15	284.50	P15	284.50
1.225"	875-K	1.175	R11	284.50	P12	347.16
1.275"	875-I	1.225	R9	265.50	P10	347.16
1.400"	D	1.350	R4	284.50	P5	347.16
1.500"	1500	1.450	---	---	P1	284.50

Price Group: SD

¹ Plain die bore diameter can be used as crimp spec ±.005
 • dies for use with 5111A and 1765A ferrule machines. Other sizes are available.

AN05