

### N-Series Dix-Lock™ Protective Nipple Cap



N-Series Bowes Interchange Protective Nipple Cap											
Body Size (inch)	Part No.	Cap Lanyard	Material	Length		Maximum OD		Weight (kg)	Pkg Qty		Price \$ (ea)
				inch	mm	inch	mm		Bag	Box	
½	N4DC	SS Steel Cable	Steel	1.50	38.10	1.33	33.80	0.15	-	25	59.82
½	N4DC-B	SS Steel Cable	Brass	1.50	38.10	1.33	33.80	0.16	-	25	77.61

Price Group: PC  
AD07


### N-Series Dix-Lock™ Replacement Seals




N-Series Bowes Interchange Replacement Seals							
Body Size (inch)	Part No.	Coupler Style	Seal Material	Seal Kit Contents	Pkg Qty		Price \$ (ea)
					Bag	Box	
¾	3N-SKIT	All	Nitrile	O-Ring	25	200	2.66
½	4N-SKIT	All	Nitrile	Pneumatically Energized Seal	25	200	0.43
½	F-4N-SKIT	All	FKM	Pneumatically Energized Seal	25	500	26.57

Price Group: PC  
AD07

### N-Series Dix-Lock™ with Ferrules



Male Head



Female Head

**Application:** Dix-Lock™ with Carbon Steel Ferrules can be crimped or swaged-on. For crimp or swage diameter recommendations refer to page 625. Rated to 150 PSI Working Pressure.

Hose Shank (inch)	Body Size (inch)	Material	Hose OD (mm)		Part No.	Price \$ (ea)
			From:	To:		
<b>Male</b>						
½	½	Steel	21	26	N4S4-WF43	86.39
¾	½	Steel	29	34	N4S6-WF63	88.54
<b>Female</b>						
½	½	Steel	21	26	4NS4-WF43	42.21
¾	½	Steel	29	34	4NS6-WF63	32.53

Price Group: PC  
AD07

FOR TECHNICAL GUIDELINES PLEASE REFER TO PAGE 249

