


NK-Series Nitto Interchange



Application:	From factory air line to pneumatic tool connection, available in various sizes and end connections. Excellent durability in any environment. An excellent general-purpose coupling for connecting factory air supply to pneumatic tool hose.
Materials:	<ul style="list-style-type: none"> Machined components are manufactured using solid steel bar stock Stainless steel balls, retaining rings and springs maximise corrosion resistance and extend service life Steel componentry is plated using chrome-over-nickel plating Available in stainless steel
Seal Components:	Nitrile (Buna-N) seals are standard, temperature range -40°C to 121°C
Interchange Data:	<ul style="list-style-type: none"> Japanese industrial interchange pneumatic coupling Nitto Kohki Hi-Cupla 200, Rectus Series 13 and CEJN Series 315

Body Size (inch)	Coupler / Plug			
	Max Working		Coupled Burst	
	PSI	bar	PSI	bar
¼	300	20	13,500	931
¾	300	20	13,500	931
½	300	20	13,500	931

G NK-Series Nitto Interchange Coupler



Body Size (inch)	Part No.	Threads (inch)	Material	Length (mm)	Max OD (mm)	Hex Size (inch)	Weight (kg)	Bag Qty	Price \$ (ea)
¼	20SF	¼ - 19 BSPP	Steel	50.0	25.0	19	0.08	10	21.19
¾	30SF	¾ - 14 BSPP	Steel	50.0	25.0	19	0.08	10	23.22
½	40SF	½ - 14 BSPP	Steel	50.0	25.0	21	0.09	5	24.40

Price Group: PC
AP10

NK-Series Nitto Interchange Nipple



Body Size (inch)	Part No.	Threads (inch)	Material	Length (mm)	Max OD (mm)	Hex Size (inch)	Weight (kg)	Bag Qty	Price \$ (ea)
¼	20PF	¼ - 19 BSPP	Steel	38.0	17.0	¾	0.03	10	4.72
¾	30PF	¾ - 14 BSPP	Steel	38.0	21.0	¾	0.04	10	5.95
½	40PF	½ - 14 BSPP	Steel	39.0	26.0	¾	0.06	5	11.16

Price Group: PC
AP10