

Hammer Unions

Features:	<ul style="list-style-type: none"> • Butt weld configurations and other materials are available, contact Dixon™ for further information. • Temperature rating: -32°C - 93°C <p>Non-shocking cold water pressure means that the rated value is the maximum pressure at ambient temperature:</p> <ul style="list-style-type: none"> • no spikes higher than this pressure. • no instantaneous pressure increases (0-2000 PSIG in ¼ of a second) • ambient temperature: 21°C
------------------	--



Hammer unions work at extremely high pressures. Mismatching components of one series with another (ie series 602 with series 1502) can lead to destruction of property, serious bodily injury or death.

D 100 Series



Application:	Used on low pressure manifolds and lines and in applications running air, water, oil or gas up to 1000 PSI NSCWP (non-shock cold working pressure).			
Feature:	Butt weld ends are schedule 80			
Colour:	Yellow sub, black nut			
Size (inch)	Configuration	NSCWP	Forged Steel	
			Part No.	Price \$ (ea)
2	FNPT Threaded	1000	HU100200	87.26
2	Welded	1000	HU100200BW	90.32
2½	FNPT Threaded	1000	HU100250	196.34
3	FNPT Threaded	1000	HU100300	240.35
4	FNPT Threaded	1000	HU100400	271.54
4	Welded	1000	HU100400BW	356.99
6	FNPT Threaded	1000	HU100600	890.54
8	FNPT Threaded	1000	HU100800	1085.93

Price Group: SD
AD08

200 Series



Application:	Used in general service applications running air, water, oil or gas up to 2000 PSI NSCWP (non-shock cold working pressure)			
Feature:	Butt weld ends are schedule 80			
Colour:	Grey sub, blue nut			
200 Series				
Size (inch)	Configuration	NSCWP	Forged Steel	
			Part No.	Price \$ (ea)
1	FNPT Threaded	2000	HU200100	38.73
1½	FNPT Threaded	2000	HU200150	149.81
2	FNPT Threaded	2000	HU200200	80.43
2	Welded	2000	HU200200BW	110.31
2½	FNPT Threaded	2000	HU200250	256.78
3	FNPT Threaded	2000	HU200300	239.81
4	FNPT Threaded	2000	HU200400	374.07
6	FNPT Threaded	2000	HU200600	1102.45
8	FNPT Threaded	2000	HU200800	2322.96

Price Group: SD
AD08

206 Series



Application:	Runs air, water, oil or gas up to 2000 PSI NSCWP (non-shock cold working pressure)			
Design:	O-ring mounted sub provides excellent sealing properties			
Colour:	Grey sub, blue nut			
Size (inch)	Configuration	NSCWP	Forged Steel	
			Part No.	Price \$ (ea)
1	FNPT Threaded	2000	HU206100	47.60
1½	FNPT Threaded	2000	HU206150	112.34
2	FNPT Threaded	2000	HU206200	75.36
2½	FNPT Threaded	2000	HU206250	223.12
3	FNPT Threaded	2000	HU206300	434.10
4	FNPT Threaded	2000	HU206400	583.67
6	FNPT Threaded	2000	HU206600	1192.07
8	FNPT Threaded	2000	HU206800	2553.56

Price Group: SD
AD08

