

Flow Boss™ Heavy Duty Washdown Gun

New Improved Design!



D

| | |
|------------------------|--|
| Application: | <ul style="list-style-type: none"> For low pressure cleaning and sanitation applications, such as food and dairy processing, tank and drum cleaning, pharmaceutical and chemical manufacturing and meat and poultry packing. |
| Specifications: | <ul style="list-style-type: none"> Flow capacity, 57 lpm at 500kpa / 72 PSI Maximum operating pressure: 2400 kpa / 350 PSI |
| Colour: | <ul style="list-style-type: none"> Blue rubber cover |
| Temperature: | <ul style="list-style-type: none"> Rubber coated handle protects hands from water temperatures to 80°C. |
| Thread: | <ul style="list-style-type: none"> ½" BSP female |
| Features: | <ul style="list-style-type: none"> Insulated covers for heat protection. All stainless steel & brass construction for superior corrosion resistance. Flow indication arrow & arrest clip. Hollow cone spray pattern |
| | <ul style="list-style-type: none"> New improved design with high flow rate. Increased strength & durability. Complete serviceability. Upgraded seal design for superior pressure tightness. Hose connects at base of gun for easy manoeuvring. Ergonomic design for operator comfort. ½" BSP female inlet. |

| Body | Part No. | Price \$ |
|----------------|----------|----------|
| Flow Boss™ Gun | DWG050A | 221.38 |

Price Group: SD
AT01

Trigger Spray Guns



Insulated Water Nozzle

| | |
|------------------------|--|
| Specifications: | <ul style="list-style-type: none"> Heavy duty brass valve and adjusting nut. Chrome plated all zinc body. Industrial strength nylon handle. Rubber head guard on threaded GHT front version. |
| Pressure: | Max. working pressure: 620 kPa/90PSI Max. flow rate: 23 L/min |
| Temperature: | Hot water up to 82°C. |
| Thread: | Inlet (handle) ¼" BSP female Outlet (nozzle attachment) ¼" GHT |
| Feature: | Hold open clip locks any spray pattern. |

| Part No. | Inlet Thread Size | Outlet Thread Size | Price \$ |
|----------|-------------------|--------------------|----------|
| SN75A | ¼" BSP | GHT | 71.45 |

Price Group: SD
AT01



Pistol-Grip Water Nozzle

| | |
|------------------------|---|
| Specifications: | <ul style="list-style-type: none"> Heavy duty all zinc metallized body. All brass valve stem and adjusting nut. Stainless steel spring with lifetime packing. Made in USA |
| Pressure: | Max. working pressure: 620 kPa/90 PSI Max. flow rate: 23 L/min |
| Thread: | Inlet (handle) ¼" BSP No outlet thread |
| Feature: | Clip locks any spray pattern. Easy squeeze on/off lever. |

| Part No. | Inlet Thread Size | Price \$ |
|----------|-------------------|----------|
| CSN75A | ¼" BSP | 18.97 |

Price Group: SD
AT01

 Do not use these products with steam lines.