

Bauer Style Couplings - Standard

D



Application:

- Irrigation suction and delivery hose connectors
- Heavy duty mining suction and delivery slurry line connectors
- Medium vacuum line connectors
- Waste water suction and delivery line connectors

Features:

- Quick connect and disconnect
- Hot dipped galvanised
- Up to 30° bending angle at the coupling joint whilst maintaining maximum flow
- Ideal for difficult sites
- Rubber seal provides an excellent seal under both pressure and vacuum
- Also available in stainless steel with oil and heat resistant seals
- Heavy duty machined tails for extra heavy duty applications where reduced distortion may be required
- Up to 20 bar working pressure

Maximum Working Pressure for Type B Couplings - Bauer Compatible	
Size (mm)	Pressure (PSI)
50 - 90	290
100 - 300	174

Lever Ring		
Size (inch)	Part No.	Price \$
2	LR3042	21.88
3	LR3043	67.54
4	LR3044	94.63
5	104125	166.93
6	LR3046	208.70
8	LR3048	319.69

Price Group: SD
AM09

Male Spigot		
Size (inch)	Part No.	Price \$
2	100050	16.09
3	100075	52.17
4	100100	71.98
5	100125	81.70
6	100150	153.44
8	100200	212.23

Price Group: SD
AM09

Female Spigot		
Size (inch)	Part No.	Price \$
2	101050	17.64
3	101075	35.82
4	101100	73.70
5	101125	93.23
6	101150	128.45
8	101200	210.52

Rubber O-ring not included

Price Group: SD
AM09