

Holedall™ Uni-Range External Couplings

Designed for smaller hose systems, these couplings may be used for hose ID's of 6mm - 25mm and come complete with factory assembled stem and ferrule combination. Can be used with Swage or Crimp equipment.

Plated Carbon Steel Stem, Ferrule				
ID & NPTF Size (mm)	Hose OD (mm)		Part No.	Price \$
	From:	To:		
6	13	15	4P1	22.76
6	15	17	4P2	96.13
6	17	18	4P3	43.17
10	18	20	6P1	64.37
10	20	21	6P2	67.79
10	21	23	6P3	45.81
15	21	23	8P1	68.77
15	23	25	8P2	55.02
15	25	30	8P3	44.79
20	29	31	12P1	41.97
20	31	32	12P2	40.78
20	32	37	12P3	37.48
25	37	39	16P1	67.50
25	39	40	16P2	63.44
25	40	42	16P3	71.89
25	42	44	16P4	81.48

Other sizes available on special order.

Price Group: PC

AU03



D

Holedall™ High Pressure Couplings

Application:	Intended for services requiring a fitting to withstand extremely high pressures (up to 3,000 PSI at 70°F) and severe operating conditions including: small and medium size drilling rigs, slim hole applications and core drill, workover, seismograph, water well, blast or shot holes.
Features:	<ul style="list-style-type: none"> • Sold as a complete coupling (stem and matching ferrule) • Must provide hose OD when ordering for a properly sized ferrule; make sure both ends of the hose are measured for OD • Must be swaged with 50 Ton or 100 Ton Ram • API and NPT sizes are interchangeable • Stems are machined from seamless pipe and tubing with specially designed serrations • Ferrules are machined from a heavy wall material incorporating matching serrations

Zinc Plated Steel Stem / Ferrule Assemblies		
ID & NPT Size (mm)	Part No.	Price \$
50	LM32-*	POR
65	LM40-*	POR
75	LM48-*	POR

* The LM fitting is sold as a complete coupling including stem and ferrule. Accurate hose OD must be provided to complete the part number and to insure proper retention.

Price Group: SD

AU03

