

Dubl-Grip® Reattachable Couplings for Pump Hose

| | |
|--------------------------|--|
| Application: | Two piece re-attachable coupling made of chrome plated brass for pump hose. Worn portion of hose can be removed and Dubl-Grip® can be applied. Easy assembly - hose is held in position by sleeve as body is threaded home. Only a wrench is required to assemble the Dubl-Grip®. Caution - reattach static wire if required. |
| Design: | Streamlined design prevents damage to hose and fits smartly on new pump equipment. Wide, flat surfaces of body threads protect inside of hose from breaking. Tapered surfaces of sleeve and body cradle hose, prevent one-point strain from flexing. Hose is gripped on its full circumference in two places, ensuring a rigid leakproof connection. |
| Working Pressure: | 300 PSI |

| Dubl-Grip® Reattachables | | |
|--|----------|----------|
| Hose ID x NPT Male x Hose OD Size (inch) | Part No. | Price \$ |
| 5/8 x 3/4 x 1 | 850212 | 99.65 |
| 5/8 x 3/4 x 1-1/32 | 850213 | 137.45 |
| 5/8 x 3/4 x 1-1/16 | 850214 | 83.81 |
| 3/4 x 3/4 x 1-1/8 | 850451 | 92.16 |
| 3/4 x 3/4 x 1-13/64 | 850455 | 95.33 |
| 3/4 x 3/4 x 1-1/4 | 850453 | 32.47 |
| 1 x 1 x 1-3/8* | 850841 | 141.01 |
| 1 x 1 x 1-7/16* | 850801 | 190.03 |
| 1 x 1 x 1-1/2* | 850811 | 181.74 |

Price Group: SD

AU05

Couplings have standard male NPT threads.

* Octagonal shape.

Refer to page 23 for Petrol Bowser Hose.

