

Single Check Valves Approved & Tested - Flanged & Grooved

Application:	Fire sprinkler systems & potable water to prevent back siphonage.
Design:	Single testable detector check valve approved.
End Connection:	Flanged - ANSI B16.1 Class 125 & drilled to AS2129 table D & E. Grooved - to AWWA C606
Materials:	Body - Ductile Iron Stem - Stainless Steel EPDM elastomers & FBE coated
Approvals:	AS 4020, AS Standards Mark certified, Watermarked & UL/FM approved
Working Pressure:	175 PSI
Temperature:	60°C



Flanged



Grooved

Face to Face Dim	Size (mm)	Part No.	TE Fire Line SCV	Price \$
420	100	SCV-100	Flanged TE	4092.40
420	100	SCV-100G	Grooved	4092.40
570	150	SCV-150	Flanged TE	6274.82
570	150	SCV-150G	Grooved	6464.38

Price Group: SD
VO03

Single Detector Check Valves with 20mm Spacer Bypass

Application:	Backflow prevention
Style:	Single Detector Check Valve spacer bypass
Options:	Also available in Flanged ends Table E

Face to Face Dim	Size (mm)	Part No.	Price \$
420	100 x 25	SCV-100X25CW	4088.11
570	150 x 25	SCV-150X25CW	6009.60

Price Group: SD
VO03



Yarra Valley Single Fireline Detector Check Valves with Metered Bypass

Application:	Backflow prevention
Style:	Single Fireline Detector Check Valve metered bypass
End Connection:	Flanged Table E

Face to Face Dim	Size (mm)	Part No.	Price \$
420	100 x 25	SCV-100X25YV	3784.03
570	150 x 25	SCV-150X25YV	7638.85

Price Group: SD
VO03



M