

## Relief Valves with Side Outlet - Fig PREL



<b>Design:</b>	This relief valve has a closed side outlet with right angle discharge. The outlet is female threaded and of the same size as the inlet.
<b>End Connection:</b>	BSP Male
<b>Body Material:</b>	Bronze
<b>Seats &amp; Trim:</b>	Bronze, SS304
<b>Temperature:</b>	-45°C to 185°C
<b>Pressure:</b>	Factory set to 1000Kpa and can be field adjusted from 300 to 1000Kpa
<b>Application:</b>	Suitable for discharge of steam, water, oil, air and liquids non-injurious to copper alloys.

Size (mm)	Part No.	Standard Setting	Price \$
15	VR-268-15	145PSI (1000 kPa)	472.52
20	VR-268-20	145PSI (1000 kPa)	513.74
25	VR-268-25	145PSI (1000 kPa)	579.65
32	VR-268-32	145PSI (1000 kPa)	730.75
40	VR-268-40	145PSI (1000 kPa)	923.05
50	VR-268-50	145PSI (1000 kPa)	1329.64

For settings other than standard, contact Dixon™.

**Price Group: SD**  
VB10

## Stainless Steel Relief Valves



<b>Design:</b>	Right angle relief valve, field adjustable.
<b>End Connection:</b>	Threaded female BSP
<b>Material:</b>	316 Stainless steel body & seat
<b>Seat:</b>	PTFE soft seat
<b>Pressure:</b>	Factory set to 1000Kpa. Field adjustable from 300 to 1000kPa
<b>Temperature:</b>	-20 to 290°C
<b>Application:</b>	Water, oil, gas, steam & corrosive fluids

Size (mm)	Part No.	Price \$
15	SRV-015	1711.28
20	SRV-020	1711.28
25	SRV-025	1711.28
32	SRV-032	4175.73
40	SRV-040	3757.36
50	SRV-050	4482.79

**Price Group: SD**  
VS01