DATA SHEET

A101 Rubber General Purpose Delivery Hose

The Right Connection®

A general-purpose air/water delivery hose, primarily used in industrial, agriculture, and construction markets where oil is not considered a significant factor.

Hose Construction

Tube:	SBR blend - black
Cover:	SBR blend - black
Reinforcing:	Polyester yarn

Features

- Weather resistant
- Oil mist resistant
- Ozone resistant
- Abrasion resistant
- Extruded

Temperature

- -20°C to 70°C

Standards

- Nil

Part Number

- To view available part number options please click here

Dimensions (mm)		Pressures				Vacuum (bar)	Bend Radius (mm)	Weight (kg/mtr)	Coil Lengths (mtr)
		Working		Burst					
ID	OD	PSI	Bar	PSI	Bar				
6.4	13.0	200	14	696	48	n/a	50	0.19	20, 100
7.9	15.0	200	14	696	48	n/a	65	0.22	20, 100
9.5	17.2	200	14	696	48	n/a	75	0.30	20, 100
12.7	22.0	200	14	696	48	n/a	100	0.47	20, 100
15.9	25.0	200	14	696	48	n/a	125	0.51	20, 100
19.1	29.4	200	14	696	48	n/a	155	0.65	20, 100
25.4	36.5	200	14	696	48	n/a	205	0.97	20, 100

Product Group: DB19