DATA SHEET

A115 Fuel Line Delivery Hose

The Right Connection®

A high quality reinforced rubber hose designed to meet the requirements of SAE 30R7, suitable for a range of applications such as flexible fuel lines, PCV connections, emission control lines, or fuel return lines. Compatible with fuels contaning a maximum of 50% aromatic content including leaded and unleaded gasoline, diesel fuel, and gasoline blends of ethanol (E-10).

Hose Construction

Tube: NBR blend - black
Cover: NBR blend, smooth - black
Reinforcing: Polyester yarn

Features

- Ozone resistant
- Weather resistant
- Oil resistant
- Extruded

Temperature

- -20°C to 70°C

Standards

- SAE 30R7

Part Number

- To view available part number options please click here

Dimensions (mm)		Pressures				Vacuum (bar)	Weight (kg/mtr)	Bend Radius (mm)	Coil Lengths (mtr)
		Working		Burst					
ID	OD	PSI	Bar	PSI	Bar				
4.8	11.0	100	7	400	28	n/a	0.12	40	30
6.4	13.0	100	7	400	28	n/a	0.15	50	30
7.9	15.0	100	7	400	28	n/a	0.19	65	30
9.5	17.0	100	7	400	28	n/a	0.23	75	30
12.7	20.0	100	7	400	28	n/a	0.28	100	30

Product Code: DB13