DATA SHEET

A200 Water Delivery Hose

The Right Connection®

AQUABOSS

With its lightweight yet durable construction this hose has been designed for use predominantly for delivery of water and non-corrosive liquids in the mining and construction industries. Also widely used for the delivery of low-pressure compressed air.

Hose Construction

Tube: SBR - black
Cover: SBR / EPDM blend - black
Reinforcing: High tensile synthetic textile cords

Features

- Ozone resistant
- Weather resistant
- Abrasion resistant
- Mylar layline & embossed tape line
- Mandrel built

Temperature

- -30°C to +80°C

Standards

- Nil

Part Number

- To view available part number options please click here

Dimensions (mm)		Pressures				Vacuum	Weight (kg/mtr)	Bend Radius (mm)	Coil Lengths (mtr)
		Working		Burst					
ID	OD	PSI	Bar	PSI	Bar	Bar			
12.7	21	150	10	435	30	n/a	0.32	127	20
19.1	27	150	10	435	30	n/a	0.45	190	20
25.4	33	150	10	435	30	n/a	0.54	255	20
31.8	41	150	10	435	30	n/a	0.79	320	20
38.1	47	150	10	435	30	n/a	0.93	380	20
50.8	60	150	10	435	30	n/a	1.14	510	20
63.5	74	150	10	435	30	n/a	1.67	635	20
76.2	87	150	10	435	30	n/a	2.07	760	20
101.6	114	150	10	435	30	n/a	2.87	1015	20
127.0	140	150	10	435	30	n/a	3.82	1270	20
152.4	164	150	10	435	30	n/a	4.21	1525	20
203.2	216	150	10	435	30	n/a	6.03	layflat	20
254.0	267	150	10	435	30	n/a	7.42	layflat	20
304.8	319	150	10	435	30	n/a	8.90	layflat	20

Product Code: DB20