DATA SHEET

A450 Petrol & Oil Delivery Hose

The Right Connection®

FUELBOSS

Specially designed for the transfer of petroleum/oil products with a maximum of 50% aromatic content. Typically used on tank trucks and in general industrial applications. Suitable for use in some reeling applications.

Hose Construction

Tube: NBR - black
Cover: SBR/EPDM blend, smooth - black
Reinforcing: High tensile synthetic textile cords with anti-static copper wire

Features

- Ozone resistant
- Weather resistant
- Abrasion resistant
- Oil resistant
- Mylar layline & embossed tape line
- Mandrel built

Temperature

- -35°C to 80°C

Standards

- Nil

Part Number

- To view available part number options please click here

Dimensions (mm)		Pressures				Vacuum (bar)	Bend Radius (mm)	Weight (kg/mtr)	Coil Lengths (mtr)
		Working		Burst					
ID	OD	PSI	Bar	PSI	Bar				
19.1	30	150	10	450	30	n/a	240	0.62	20
25.4	37	150	10	450	30	n/a	300	0.82	20, 60
31.8	44	150	10	450	30	n/a	385	1.05	20, 60
38.1	51	150	10	450	30	n/a	455	1.29	20, 60
50.8	64	150	10	450	30	n/a	610	1.64	20
63.5	75	150	10	450	30	n/a	760	1.76	20
76.2	90	150	10	450	30	n/a	910	2.47	20

Product Code: DB13