DATA SHEET

A635 Milk & Beverage Suction & Delivery Hose



Highly flexible spiral-reinforced hose designed for managing the transportation and transfer of milk, loading and unloading tankers, dairy unloading bays and equipment within processing and filling facilities. This versatile hose is also suitable for conveying alcoholic beverages containing up to 36% alcohol content including beer, wine and cider, along with a variety of additional liquid food products, including soft drinks, fruit juices, and potable water.



Hose Construction

Tube: NR food grade - white

Cover: NR blend smooth (wrapped finish) - blue **Reinforcing:** High tensile synthetic textile cords, double

embedded steel wire helix

Features

- Food grade FDA
- Abrasion resistant
- Weather resistant
- Ozone resistant
- Mylar layline & embossed tape line
- Tube resistant to 36% alcohol content
- · Mandrel built

Temperature

- -40°C to 95°C
- Steam cleaning without pressure up to 130°C/max. 30 min.

Standards

 FDA title 21 art.177.2600 (e) for liquid foods, BfR, KTW, PHTHALATE free.

Part Number

• To view available part number options please click here

Dimensions (mm)		Pressures				Bend	.,		
		Working		Burst		Radius	Vacuum (bar)	Weight (kg/mtr)	Coil
ID	OD	PSI	Bar	PSI	Bar	(mm)	(34.7)	(9,)	Lengths
IO)(€	(mtr)
19.1	30.0	90	6	270	18	120	0.9	0.60	20
25.4	37.0	90	6	270	18	150	0.9	0.80	20
31.8	44.0	90	6	270	18	225	0.9	1.10	20
38.1	52.0	90	6	270	18	300	0.9	1.40	20
50.8	65.0	90	6	270	18	350	0.9	2.30	20
63.5	80.0	90	6	270	18	400	0.9	3.10	20
76.2	93.0	90	6	270	18	450	0.9	3.50	20
101.6	120.0	90	6	270	18	500	0.9	5.00	20

Product Code: DB36