Betts Wet-R-Dri™ Valve

Easily mounted in any position

Application

Designed for handling liquid, gaseous, or dry products

Features

- · Has a positive stop in the open and closed position
- Detent spring and ball assist in holding the disc in the open and closed position
- · Drilling fits TTMA recommended standards
- Opens by turning hand 1/4 turn counter clockwise

Specification

• Temperature range: 0°F to 400°F (-18°C to 204°C)

Manual

Size	Maximum Working Pressure PSI	Extruded aluminum body with FKM-B disc Part #
2"	75	WD201ALVB
3"		WD301ALVB
4"		WD401ALVB
5"		WD501ALV
6"		WD601ALV
8"		WD801ALV

Metering

Size	Maximum Working Pressure PSI	Extruded aluminum body with FKM-B disc Part #
2"	75	WD206ALVB
3"		WD306ALVB
4"		WD406ALVB
5"		WD506ALV
6"		WD606ALV
8"		WD806ALV

Replacement Handle

Part #	Extruded aluminum body with FKM-B disc Part #
28967ALEY	replacement handle for 2", 3", 4", and 5" manual handle valves
25933AL	replacement handle for 6" and 8" manual handle valves
28981ALEY	replacement handle for 2", 3", 4", and 5" metering handle valves
26287AL	replacement handle for 6" and 8" metering handle valves

NOTE: For flange dimensions, diagrams and additional information please reference dixonvalve.com.

© 2022 DVCC • WETWRDRI_322

