DATA SHEET H020 TPR/Food Grade Delivery Hose



Manufactured from high-quality PVC, boasting outstanding flexibility, featuring a glass-clear translucent appearance with a hint of blue, ensuring excellent visibility of transferred products. This versatile hose is perfectly suited for a wide range of applications, including the transfer of air, water, food and beverage items, as well as petroleum products. It finds utility across various industries such as food production, mining, construction, general industrial and agricultural sectors. Not suitable as a permanent fuel line.



Hose Construction

Tube:	
Cover:	

PVC - transparent PVC smooth - transparent **Reinforcing:** Polyester yarn, red spiral tracer

Special Features

- UV stabilised
- Abrasion resistant
- Food grade FDA
- Oil mist resistant

Temperature

• -5°C to 60°C

Standards

AS/NZS 2554 Class B

Part Number

• To view available part number options please click here

Dimensions (mm)		Pressures				Bend			
		Working		Burst		Radius	Vacuum (bar)	Weight (kg/mtr)	Coil
ID	OD	PSI	Bar	PSI	Bar	(mm)	(/	(Lengths
IO	\bigcirc		\mathcal{D}		\bigcirc)((mtr)
6.40	12.0	232	16	928	64	75	n/a	0.12	20, 100
7.90	14.0	232	16	928	64	95	n/a	0.16	20, 100
9.50	16.0	232	16	928	64	120	n/a	0.18	20, 100
12.7	19.0	232	16	928	64	150	n/a	0.22	20, 100
15.9	24.0	232	16	928	64	180	n/a	0.32	20, 100
19.1	28.0	232	16	928	64	240	n/a	0.47	20, 100
25.4	35.0	232	16	928	64	300	n/a	0.65	20, 100
31.8	43.0	150	10	600	40	385	n/a	0.88	20, 100
38.1	50.5	150	10	600	40	480	n/a	1.12	20, 100
50.8	63.5	150	10	600	40	600	n/a	1.60	20, 100
								Produ	ct Code: DA01