
## ORDERING GUIDE Spring Balanced Loading Arms





Custom options are available. Contact Dixon Specialty Products at 888.226.4673 or dspsales@dixonvalve.com.

• Uncommon Excellence • Uncommon

## **Section 4: Leg Measurements and Materials**

Measure legs as indicated in graphic below - centerline of swivel to centerline of swivel (standard), and round to the nearest inch. If measuring flange to flange (non-standard), **PLEASE NOTE** somewhere on this page. Please be sure to refer to A, B, and Boom/Scissor legs correctly, as indicated in the graphic below.

Le	g A length: N	laterial:	carbon st	eel		aluminum		316 stainle	ess s	teel		
Le	g B length: N	Material: carbon						316 stainle	316 stainless steel			
		Material: carbon steel				aluminum (scissor onl	316 stainless steel			el		
	- TAI		Leq B Length	Leg A	Scisso	₽₹	Boom	Eeg Leg	A		Leg B	
	ction 5: Load Arm Inf	ormation	I									
a.	Quantity:					_						
b.	Pipe size: 2"	3"	4"	6"		other :		"				
C.	c. Base swivel: split flange style V-ring style (carbon steel only) NOTE: Swivel materials are based on leg materials. For non-standard requests, please contact the factory.											
d.	Riser stand pipe connection	n: Cla	ass 150 ANSI f	lange		Class 300 A	NSI f	lange	0	ther :	:	
e.	Type of media: aspha	lt fu	uel ot	her :								
f.	Seals (Dixon can recommend based on media): Nitri				rubber			PTFE F			KM-A	
FDA nitrile			e	Low tem	perat	ure FKM	EPDM oth			r:		
g.	Environment conditions: Temperature range °F to °F Operating PSI :											
h.	End connections (check all that apply): i. Add-ons (check all that apply):											
	45° pipe cut		cam & groove c	oupler		top loading va	alve				sight glass	
	API coupler w/ flange extensio	n	cam & groove adapter		top loading valve w/			// remote handle kit			D-handle	
	tee-deflector		diffuser		butterfly (Wet-R-Dri™) valve						ball handle	
	male NPT		dry disconnect (DDC)			split flange locking mechanism					bucket hook	
	other.		dry break coupl		loading arm handle					safety breakaway		
TTMA fla				TMA flange		top loading lock bar					grounding	
j. Site limitations, such as distance from ceiling or roof to						hose cover					heat tracing	
	riser pipe:					replacement	flange	kit (extra line i	item)		color coded TTMA ext.	
<ul> <li>Additional items being added by the customer and estimated weight:</li> </ul>						replacement seal kit (extra line item)					color (s): other :	
	· · · · · · · · · · · · · · · · · · ·							Dixon \$	Spe	ecia	Ity Products	
Not	Notes:					225 Talbot Blvd. Chestertown, MD 21620 ph: 888.226.4673 fx: 410.778.1958						
Cus	Custom options are available. Contact us at dspsales@dixonvalve.com.								dixonvalve.com © 2023 DVCC • LAOG323 inhouse			



