Dixon® Fire Specification Sheet Nitrile Washdown Hose



Nitrile Washdown Hose

Application

 Ideal for industrial, agricultural, and construction washdown and discharge applications, not for fire fighting

Feature

• Resistant to weather and abrasion



Uncoupled

Size	Color	Bowl	Length	Working Pressure	Part #
1"	black	1-1/4"	50'		WDH10BK50UC
			100'		WDH10BK100UC
	yellow	1-1/4"	100'		WDH10Y100UC
	blue	1-1/4"	100'		WDH10BL100UC
1-1/2"	black	1-13/16"	50'	200 DCI	WDH15BK50UC
			100'	200 PSI	WDH15BK100UC
2"	black	2-5/16"	50'		WDH20BK50UC
			100'		WDH20BK100UC
2 1 /2"	black	2-13/16"	50'		WDH25BK50UC
2-1/2"			100'		WDH25BK100UC
3"	black 3-3	2.2/0"	50'		WDH30BK50UC*
		3-3/8"	100'		WDH30BK100UC*
4"	black	4-3/8"	50'	150 DCI	WDH40BK50UC*
			100'	150 PSI	WDH40BK100UC*
6"	blask	black 6-3/8"	50'		WDH60BK50UC*
	ріаск		100'		WDH60BK100UC*

^{*}Stock quantity only

Nitrile Washdown Hose

Technical Information



Nitrile Washdown Hose

Application

• Ideal for industrial, agricultural, chemical, and construction washdown and discharge applications, not for fire fighting

Feature

· Resistant to weather and abrasion

Coupled with NPSH female and male King™ short shank couplings, crimp sleeve, aluminum shank with brass pin lug swivel nut



Size	Length	Part #
1 1 /0"	25'	WDH15BK25KAS
1-1/2"	50'	WDH15BK50KAS
2"	25'	WDH20BK25KAS
Z	50'	WDH20BK50KAS
1 /0"	25'	WDH25BK25KAS
2-1/2"	50'	WDH25BK50KAS
0"	25'	WDH30BK25KAS
3"	50'	WDH30BK50KAS

Coupled with NST (NH) female and male King short shank couplings, crimp sleeve, aluminum shank with brass pin lug swivel nut



Size	Length	Part #
1-1/2"	25'	WDH15BK25KAF
1-1/2	50'	WDH15BK50KAF
2-1/2"	25'	WDH25BK25KAF
Z-1/Z	50'	WDH25BK50KAF

Coupled with female and male (C & E) global aluminum cam and groove, crimp sleeve



Size	Length	Part #
1 /0"	25'	WDH15BK25GAX
-1/2"	50'	WDH15BK50GAX
2"	25'	WDH20BK25GAX
Z	50'	WDH20BK50GAX
-1/2"	25'	WDH25BK25GAX
1/2	50'	WDH25BK50GAX
O.I.	25'	WDH30BK25GAX
3"	50'	WDH30BK50GAX
4 "	25'	WDH40BK25GAX
4"	50'	WDH40BK50GAX

Nitrile Washdown Hose

Technical Information



Nitrile Washdown Hose

Application

 Ideal for industrial, agricultural, and construction washdown and discharge applications, not for fire fighting

Feature

· Resistant to weather and abrasion

Specification

- Working pressure: 200 PSI
- Working temperature: -4°F to 158°F (-20°C to 70°C)

Coupled with NPSH female and male expansion ring couplings

Size	Length	Part #
1-1/2"	50'	WDH15BK50RAS
1-1/2	100'	WDH15BK100RAS
2"	50'	WDH20BK50RAS
Z	100'	WDH20BK100RAS
2-1/2"	50'	WDH25BK50RAS
2-1/2	100'	WDH25BK100RAS



Coupled with NST female and male expansion ring couplings

Size	Length	Part #
1-1/2"	50'	WDH15BK50RAF
1-1/2	100'	WDH15BK100RAF
	25'	WDH25BK25RAF
2-1/2"	50'	WDH25BK50RAF
	100'	WDH25BK100RAF



Coupled with MNPT x MNPT male expansion ring couplings

Size	Length	Part #
1-1/2"	50'	WDH15BK50RAT
1-1/2	100'	WDH15BK100RAT
2"	50'	WDH20BK50RAT
2	100'	WDH20BK100RAT



Dixon Fire

325 Arbor Ct Winchester, VA 22602 ph: 877.963.4966 fx: 800.283.4966 dixonvalve.com