

Dixon EZLink™ Armless Cam & Groove

Push-to-connect, low profile, positive locking system and more!



Assembled with 6200 series elbow

Patent Pending

Applications:

- Transfer and/or unloading of fuels (gasoline or diesel) from tank truck to storage tanks
- Transfer of liquids compatible with the available coupling and gasket materials

Materials:

- Couplings and dust caps: A356 aluminum, 316 stainless steel
- · Coupler tabs and springs: 316 stainless steel
- Gasket: Buna-N

Features:

- Automatic couplers push-to-connect providing a reliable connection
- Low profile allows easy connection and disconnection in tight applications
- · Coupler push tabs can be locked with safety pins and/or zip tie
- · Compatible with standard cam and groove adapters

Specifications:

- Maximum working pressure with King Crimp™ ferrules: 250 PSI (2"), 150 PSI (3" and 4")
- 4" maximum working pressure with crimp sleeves: 110 PSI
- 4" maximum working pressure with band clamps: 100 PSI
- Gasket temperature range: 5°F to 180°F (-15°C to 82°C)

A

Warning: Only use EZLink™ gaskets for this coupling system. Traditional cam & groove gaskets, or other types of seals are not compatible and will fail.

Type B Coupler x Male NPT

Size	A356 Aluminum	316 Stainless Steel
	Part #	Part #
2"	EZL200-B-AL	EZL200-B-SS
3"	EZL300-B-AL	
4"	EZL400-B-AL	
		_



Type C Coupler x King Crimp™ Hose Shank

Size	A356 Aluminum	316 Stainless Steel
	Part #	Part #
2"	EZL200-C-AL	EZL200-C-SS
3"	EZL300-C-AL	
4"	EZL400-C-AL	



Type D Coupler x Female NPT

Size	A356 Aluminum	316 Stainless Steel
	Part #	Part #
2"	EZL200-D-AL	EZL200-D-SS
3"	EZL300-D-AL	
4"	EZL400-D-AL	



Type DC Dust Caps

Size	A356 Aluminum	316 Stainless Steel
	Part #	Part #
2"	EZL200-DC-AL	EZL200-DC-SS
3"	EZL300-DC-AL	





Replacement Kits

· kit contains: 2 pins, 2 springs and 2 tabs

Size	A356 Aluminum
	Part #
2"	EZL200RPLKIT
3" and 4"	EZL300RPLKIT



Replacement Gaskets

Size	Buna-N
	Part #
2"	EZL200-G-BU
3"	EZL300-G-BU
4"	EZL400-G-BU



Safety Clip

Plated Carbon Steel Part #

EZLCL400



















800 High Street • Chestertown, MD 21620 ph 877.963.4966 • fx 800.283.4966

dixonvalve.com



YouTube



Dixon Customer Service