# **NATION SHEET**King Cable™ Safety Whipcheck



King Safety cables prevent hose whip in the event of the accidental separation of a coupling or clamp device. The steel cables span the hose fittings to provide standby safety for the hose. Spring-loaded loops in the cable ends are easily opened to passover the couplings and provide a firm grip on the hose.





# **Features**

- King safety cable reaches across the hose fittings to provide safety for hose application
- Thoroughly tested with years of service. A positive safeguard for hose connections - helps you meet today's safety standards
- · Highly resistant to rust and corrosion
- Minimises damage to equipment and injuries to operators in the event hose, couplings or clamps fail, or there is an accidental separation of the assembly
- · Hose-to-hose or hose-to-rigid outlet

## Construction

- · Wire Rope Galvanised Carbon Steel
- · Ferrules Aluminium
- · Springs Galvanised Carbon Steel

# **Installation and Safety Notes**

- Must be installed in the extended position (no slack)
- · No tools needed easy to install and remove

# **HOSE-TO-TOOL SERVICE**

Size			Maximum Working Pressure	Part #	
Cable (mm)	Hose ID (mm)	Length (mm)	PSI	Steel	Stainless Steel
3	13 - 32	515	200	WSR1	WSR1SS
5	13 - 50	712	200	WSR3	-
6	38 - 75	956	200	WSR2	WSR2SS
10	100	1118	200	WSR4	-

# **HOSE-TO-HOSE SERVICE**

Size			Maximum Working Pressure	Part #	
Cable (mm)	Hose ID (mm)	Length (mm)	PSI	Steel	Stainless Steel
3	13 - 32	515	200	WB1	WB1SS
5	13 - 50	712	200	WB3	-
6	38 - 75	956	200	WA2	WA2SS
10	100	1118	200	WA4	-

# **Dixon**

1300 134 651

customerser vice @dixonval ve.com. au

dixonvalve.com.au