# <sup>116</sup> Minsup™ Fittings

## 'A' Type - Standard Seal 500 PSI - SG Iron minsup

Three Way


С



Blank End



20 08/001/16/000 AWR4 Standard 45.15   Price Group: MS   AA01	Pkg Qty	Part No.	Seal Type	Price \$ (ea)
	20	08/001/16/000	AWR4 Standard	45.15
				Price Group: MS AA01



#### Price Group: MS

AA01

## 'A' Type Medium Surelock™ Adaptor

Application	Enables easy connection b	Enables easy connection between Minsup™ A Type and Medium Surelock™ (1½" to 2")		
Pkg Qty	Part No.	Seal Type	Price \$ (ea)	
1	08/013/32/000	AWR4 Standard	115.86	

### Price Group: MS

AA01

## 'A' Type Standard Seals

Pkg Qty	Part No.	Material	Price \$ (ea)
50	AWR4	Natural Rubber	1.35
1	AWR4V	FKM	8.10

#### Price Group: SD

AD05





Pkg Qty	Part No.	Material	Price \$ (ea)
1000	05/010/02/000	Z/P mild steel	0.40
1000	05/010/02/000SS	316 Stainless Steel	2.70

#### Price Group: MS BA01



The use of a Minsup<sup>™</sup> Safety Locking Pin is necessary to ensure that Minsup<sup>™</sup> A Type & Surelock<sup>™</sup> Claw Couplings will not become accidentally disconnected. This ensures that the fittings are properly connected as the pin will not go through the holes in both couplings until the couplings are locked into place.

Gauze



Application: Eliminates air line debris from damaging in-line air		ools or valve seals.
	Part No.	Price \$ (ea)
	05/100/01/901	6.75
		Price Group:

Group: SD AA01

FOR SPECIFICATIONS, APPLICATION AND MATERIAL GUIDELINES PLEASE REFER TO PAGE 114

