63mm Diameter Pressure Gauges

Features:	Water-proof, shock resistant and closed structures are durable and accurate. All series are liquid-filled – Glycerine filled.
Materials:	Stainless steel case. Brass, bourdon tube.
Specifications:	 Model: 323 Series. (Crimped On Bezel-CB) Case: AlSI 304 S/S Type: Pressure Gauge Nominal Size: 63mm Tubing: Brass Movement: Brass Connection: Brass ¼" BSPT Pointer Type: General Accuracy: ± 1.5%F.S. (READ ANSI-B40.1 1985) Scale: Dual scale PSI and kPa.



D

I	Part No.	Pressure Range		Price \$	Part No.	Pressure Range		Price \$
		PSI	kPa	(ea)	Part No.	PSI	kPa	(ea)
	PG00030	0 - 35	0 - 250	30.10	PG01000	0 - 1,160	0 - 8,000	32.46
	PG00060	0 - 55	0 - 400	31.65	PG02000	0 - 2,300	0 - 16,000	47.98
	PG00085	0 - 85	0 - 600	31.89	PG03500	0 - 3,500	0 - 24,100	30.49
	PG00100	0 - 115	0 - 800	31.00	PG05800	0 - 5,800	0 - 40,000	55.92
	PG00160	0 - 145	0 - 1,000	30.40	PG06000	0 - 6,000	0 - 41,400	61.07
	PG00200	0 - 230	0 - 1,600	31.84	PG08000	0 - 8,000	0 - 55,200	55.95
	PG00360	0 - 360	0 - 2,500	33.88	PG10000	0 - 10,000	0 - 69,000	40.95
	PG00600	0 - 600	0 - 4,100	32.78	PGAUGEVACCUM	N/A	-100	83.51
	PG00800	0 - 870	0 - 6,000	30.62				

Other varieties of pressure gauges available on request.

Price Group: SD

AN09

FP05

100mm Diameter Pressure Gauges

Application:	Light weight, low cost gauge is primarily used in fire protection hydrant assemblies, or where pressure is generally static.			
Materials:	Black steel casing, glass face. Brass Bourdon tube.			
	 Pressure gauges are available with 65mm face, liquid filled and in other configurations. Other varieties of pressure gauges available on request. 			

Part No.	Casing	BSP Inlet Size (inch)	Pressure Range kPa	Price \$ (ea)
PG-100-1600	black steel	3/8	0 - 1600	136.05
PG-100-2500	black steel	3/8	0 - 2500	99.25
PG-100-2500-1/2	black steel	1/2	0 - 2500	51.38
PG-100-2500-SS	00-2500-SS stainless steel 3/8		0 - 2500	150.65
				Price Group: SD



