

## Rubber Super Air & Water Delivery Hose (A190)

<b>Application:</b>	Mandrel built air hose suitable for a variety of industries including construction sites and mines.
<b>Tube:</b>	SBR, black smooth, oil mist resistant
<b>Reinforcement:</b>	High strength synthetic cord
<b>Cover:</b>	Black/yellow with blue stripe (wrapped finish), long lasting EPDM rubber, weather and ozone resistant
<b>Temperature:</b>	-30°C to 70°C
<b>Special Features:</b>	<ul style="list-style-type: none"> <li>Ozone resistance</li> <li>Minimum cut length of 5 mtrs, charges apply for cutting hose.</li> </ul>




Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius (mm)	Weight kg/mtr	Length mtr	Price \$ per mtr
	ID	OD	PSI	MPa					
<b>Black</b>									
A190012	13	23	300	2.1	900	60 <sup>1</sup>	0.37	20	15.24
A190020	19	29	300	2.1	900	90 <sup>1</sup>	0.55	20	19.75
A190025	25	35	300	2.1	900	120 <sup>1</sup>	0.59	20, 60	25.95
A190032	32	44	300	2.1	900	250 <sup>1</sup>	0.92	20	30.46
A190040	38	50	300	2.1	900	310 <sup>1</sup>	1.16	20	37.23
A190050	51	65	300	2.1	900	450 <sup>1</sup>	2.21	20	50.78
A190080	76	91	300	2.1	900	725 <sup>1</sup>	3.40	20	84.62
A190100	102	122	300	2.1	900	950 <sup>1</sup>	4.38	20	150.07
<b>Yellow</b>									
A190012Y	13	23	300	2.1	900	60 <sup>1</sup>	0.37	20	15.24
A190020Y	19	29	300	2.1	900	90 <sup>1</sup>	0.55	20	19.75
A190025Y	25	35	300	2.1	900	120 <sup>1</sup>	0.59	20	24.82
A190032Y	32	44	300	2.1	900	250 <sup>1</sup>	0.92	20	33.84
A190040Y	38	50	300	2.1	900	320 <sup>1</sup>	1.16	20	36.11
A190050Y	51	65	300	2.1	900	450 <sup>1</sup>	2.21	20	51.90
A190080Y	76	91	300	2.1	900	725 <sup>1</sup>	3.40	20	84.62
A190100Y	102	122	300	2.1	900	950 <sup>1</sup>	4.38	20	169.24

Price Group: HR

DB03

## Super Air & Water Delivery Hose Assembly (A190)

Black/Blue Stripe									
Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius (mm)	Weight kg/mtr	Length mtr	Price \$ per mtr
	ID	OD	PSI	MPa					
<b>Minsup™ Surelock™ with Claw Clamps</b>									
A19005020F	51	65	300	2.1	900	450 <sup>1</sup>	2.21	20	1590.87
<b>Minsup™ A Type with Claw Clamps</b>									
A19001220F	13	23	300	2.1	900	60 <sup>1</sup>	0.37	20	423.10
A19002520F	25	35	300	2.1	900	120 <sup>1</sup>	0.59	20	625.07
<b>Minsup™ Surelock™ with Claw Clamps</b>									
A19002520FSL	25	35	300	2.1	900	120 <sup>1</sup>	0.59	20	626.20



Black Minsup™ assembly with claw clamps



Black Minsup™ assembly with claw clamps



Yellow Minsup™ assembly with claw clamps

Yellow/Blue Stripe									
Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius (mm)	Weight kg/mtr	Length mtr	Price \$ per mtr
	ID	OD	PSI	MPa					
<b>Minsup™ Surelock™ with Boss™ Clamps</b>									
A190050Y20F	51	65	300	2.1	900	450 <sup>1</sup>	2.21	20	1449.84

<sup>1</sup> Denotes figure is calculated as theoretical.

Price Group: HR

DB03

Complete hose data specification sheets are available upon request.



1300 134 651  
dixonvalve.com.au

All prices exclude GST.  
ADPL718