Industrial Hose Fittings 165

Economy Hose Reels

Application:

Economy Hose Reels for domestic and industrial applications. Used primarily with PVC hoses, refer to the PVC Hose section of this catalogue.

| Part No. | Suits | Colour | Inlet (mm) | Outlet (inch) | Price \$ (ea) |
|----------|-------------------|--------|---------------|------------------|------------------|
| Standard | | | | | |
| SR3012 | 30mtr x 12mm Hose | Green | 12 | 1/2 | 390.57 |
| SR5012 | 50mtr x 12mm Hose | Green | 12 | 1/2 | 467.37 |
| SR4018 | 40mtr x 18mm Hose | Black | 18 | 3/4 | 505.55 |
| LR6018 | 60mtr x 18mm Hose | Black | 18 | 3/4 | 660.00 |
| Mobile | | | | | |
| SM5012 | 50mtr x 12mm Hose | Green | 12 | 1/2 | 666.72 |
| SM4018 | 40mtr x 18mm Hose | Black | 18 | 3/4 | 578.38 |
| LM6018 | 60mtr x 18mm Hose | Black | 18 | 3/4 | 850.35 |



^{*} Refer to page 143 for swivels to suit the economy hose reels. Two swivels required per hose reel.



Price Group: SD

FP06



Standard



Mobile

Dixon™ Heavy Duty Hose Reel

| Application: | Improves hose handling, prolongs hose life, reduces trip hazards. |
|--------------|--|
| Colour: | Yellow for high visibility |
| Material: | Manufactured from mild steel |
| Capacity: | Approximately 40 metres (25 mm hose) |
| Wheel: | Diameter: 700 mm, Depth: 650 mm, Height: 820 mm |
| Optional: | Optional swivel attachment allows the hose reel to swivel 180° for improved coverage and ease of use. Swivel can be locked. |
| Design: | Re-engineered design with new innovative assembly provides following advantages: • rapid centre pin replaces fiddly bolts for reduced assembly time • no more bolt alignment issues • improved hose support when reeled, less chance of kinking • increased hose capacity • ability to dismantle and service without unwinding hose |

| Part No. | Description | WP PSI (Water) | WP PSI (Air) | Inlet (nb) | Outlet (nb) | Price \$ (ea) |
|----------|-------------------------------|-------------------|-----------------|---------------|----------------|------------------|
| HR-HDW | Heavy Duty Hose Reel Standard | 300 | 200 | 25 | 25 | 1128.05 |
| HR-HDWS | Swivel Attachment (Optional) | - | - | - | - | 697.20 |

Price Group: SD

AT01

New improved design!



Optional swivel attachment

High-Flow Washdown Hose Reel

| Features: | Suitable for mounting to wall, floor, vehicles or transportable |
|-----------------|--|
| | Light weight, compact and easy to move |
| | 19 mm hose for increased water flow |
| | Various commercial, marine and domestic wash-down applications and may also be used to assist in extinguishing small scrub fires. |
| | Rugged construction |
| | Comes complete with rewind handle and flexible inlet connection that screws onto a standard garden tap. |
| Specifications: | Dimension: 520 mm x 410 mm x 520 mm (LxWxH) Weight: 14 kg Material: Mild Steel Hose Material: PVC to Australian Standard AS1221 Nozzle: Jet / Spray / Off Capacity: 19 mm x 25 m hose Finish: Epoxy Powder Yellow, 70 micron min |



Price Group: FE

FP06



