

## External Swage Stems

Designed for hose ID's 32mm - 250mm. The ferrule size depends on the hose OD. Refer to page 200 for selection of the correct ferrule. Stems and ferrules are supplied in plated carbon steel and stainless steel.

Carbon Steel (Male NPT)			Plated Carbon Steel (Male BSP)		Unplated Carbon Steel Bevelled End (for Welding)	
Size (mm)	Part No.	Price \$	Part No.	Price \$	Part No.	Price \$
32	TM20	92.04	TM20A	POR	TP20	572.66
40	TM24	71.58	TM24A	114.19	TP24	107.38
50	TM32	78.68	TM32A	81.81	TP32	107.38
65	TM40	112.49	---	---	TP40	117.61
75	TM48	127.83	TM48A	168.74	TP48	141.26
100	TM64	203.61	TM64A	209.64	TP64	161.20
125	TM80	255.65	TM80A	POR	TP80	260.77
150	TM96	311.90	TM96A	POR	TP96	177.32
200	TM128	306.78	TM128A	POR	TP128	409.05



Style TM & TML  
NPT end & BSP end.



Style TP & TPL  
Plain end. Unplated.

Price Group: SD  
AU03

## Dixon™ Hookie Hook External Crimp Hose Stem

Material:	Carbon Steel
-----------	--------------

Part No.	Size (inch)	Price \$
TM48GR	3	521.90
TM64GR	4	246.60
TM80GR	5	1502.20
TM96GR	6	POR



Price Group: SD  
AU03

## Dixon™ Hookie Hook Lifter

Application:	Predominantly used for bulk loading/rig supply hose operations on offshore applications
Material:	Forged carbon steel, yellow zinc plated per BS1706
Options:	With or without retaining clamp
Load Rating:	Safe working load 4 tons with a proof load test of 8 tons

Part No.	Size (inch)	Price \$
HA0900-3	3	679.83
HA0900-4	4	679.83
HA0900-5	5	679.83



Price Group: SD  
AU03