

## Rubber Single LPG Hose (A110)

<b>Application:</b>	For conveying LPG in household and industrial applications. Used for gas cutting application.
<b>Tube:</b>	NBR
<b>Reinforcing:</b>	Polyester
<b>Cover:</b>	PVC / NBR Orange
<b>Temperature:</b>	-20°C to 75°C
<b>Features:</b>	Minimum cut length of 5 mtrs, charges apply for cutting hose.
<b>Standards:</b>	AS/NZS1869 Class C



Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius (mm)	Weight kg/mtr	Coil Lengths	Price \$ per mtr
	ID	OD	PSI	MPa					
A11005	5	13	375	2.6	1500	60 <sup>1</sup>	0.18	2 x 100M Reels	6.18
A11006	6	14	375	2.6	1500	72 <sup>1</sup>	0.20	2 x 100M Reels	8.05
A11010	10	18	375	2.6	1500	120 <sup>1</sup>	0.28	2 x 100M Reels	9.79

Price Group: HR  
DB23

## Rubber Air Brake Hose (A103)

<b>Application:</b>	Extruded rubber hose for the conveyance of air in truck brake systems. Reinforced with a single spiral polyester yarn.
<b>Tube:</b>	EPDM
<b>Reinforcement:</b>	4 spiral polyester yarn
<b>Cover:</b>	EPDM
<b>Temperature:</b>	-35°C to 75°C
<b>Features:</b>	Minimum cut length of 5 mtrs, charges apply for cutting hose.
<b>Standards:</b>	According to SAE J1402 (Table 1, Type A), Synthetic Oil Resistant Compound



Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius (mm)	Weight kg/mtr	Length mtr	Price \$ per mtr
	ID	OD	PSI	MPa					
A103010	10	19	290	2	870	120 <sup>1</sup>	0.38	152	6.92
A103012	13	22	290	2	870	156 <sup>1</sup>	0.39	152	7.76

Price Group: HR  
DB33

<sup>1</sup> Denotes figure is calculated as theoretical.

Complete hose data specification sheets are available upon request.