

## PVC Safety Yellow Air Water Delivery (H010)

<b>Application:</b>	General purpose air water delivery with excellent flexibility and toughness. Resistant to oils.
<b>Tube:</b>	Black smooth PVC
<b>Reinforcing:</b>	High tensile synthetic yarns
<b>Cover:</b>	Yellow ribbed PVC
<b>Temperature Range:</b>	0°C to 60°C
<b>Special Features:</b>	• UV stabilised
<b>Standards:</b>	Conforms to and exceeds AS2554 Class A




Part No.	Dimensions (mm)		Pressure				Bend Radius	Weight kg/mtr	Length (mtr)	Price \$ per mtr / coil
			Positive PSI/Bar							
			Working		Burst					
ID	OD	PSI	Bar	PSI	Bar					
H01006100	6	11.4	300	20	1200	80	60	0.10	100	231.14
H0100820	8	14.4	300	20	1200	80	80	0.15	20	54.22
H01008100	8	14.4	300	20	1200	80	80	0.15	100	270.95
H0101020	10	16.4	300	20	1200	80	100	0.18	20	59.69
H01010100	10	16.4	300	20	1200	80	100	0.18	100	297.50
H0101220	12.5	18.9	300	20	1200	80	125	0.22	20	71.76
H01012100	12.5	18.9	300	20	1200	80	125	0.22	100	358.82
H0102020	20	27.8	300	20	1200	80	200	0.40	20	124.16
H01020100	20	27.8	300	20	1200	80	200	0.40	100	620.82
H0102520	25	35	300	20	1200	80	250	0.61	20	201.39
H01025100	25	35	300	20	1200	80	250	0.61	100	1013.83
H0103220	32	44	300	20	1200	80	320	0.87	20	353.13
H0103260	32	44	300	20	1200	80	320	0.87	60	1059.73
H0104020	40	51	300	20	1200	80	400	0.97	20	473.88
H0104060	40	51	300	20	1200	80	400	0.97	60	1751.83
H0105020	50	63.5	300	20	1200	80	500	1.52	20	774.61

Price Group: HP  
DA28

## PVC Safety Yellow Air Water Delivery Assembly (H010)

<b>Application:</b>	General purpose air water delivery with excellent flexibility and toughness. Resistant to oils.
<b>Tube:</b>	Black smooth PVC
<b>Reinforcing:</b>	High tensile synthetic yarns
<b>Cover:</b>	Yellow ribbed PVC
<b>Temperature Range:</b>	0°C to 60°C
<b>Special Features:</b>	• UV stabilised
<b>Standards:</b>	Conforms to and exceeds AS2554 Class A



Part No.	Dimensions (mm)		Pressure				Bend Radius	Weight kg/mtr	Length (mtr)	Price \$
			Positive PSI/Bar							
			Working		Burst					
ID	OD	PSI	Bar	PSI	Bar					
H0101220F	12.5	18.9	300	20	1200	80	125	0.22	20	132.89
H0102020F	20	27.8	300	20	1200	80	200	0.40	20	174.55
H0102520F	25	35	300	20	1200	80	250	0.65	20	202.76

Complete hose data specification sheets are available upon request.

