

A PVC Superflex Yellow / Blue




Application:	General purpose air & water supply with superior flexibility & toughness. Resistant to oil.
Tube:	PVC (Poly Vinyl Chloride)
Reinforcing:	High strength polyester braid
Cover:	PVC (Poly Vinyl Chloride)
Temperature:	0°C to 60°C
Special Features:	UV stabilised
Standards:	¼" to 1½" - Exceeds AS/NZS 2554:1998 Class B for burst pressure 2" - Exceeds AS/NZS 2554:1998 Class C for burst pressure
Design:	Designed for air, water
Construction:	Yellow ribbed cover with blue smooth stripe, black tube

Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius	Weight kg/mtr	Length (mtr)	Price \$ per coil
	ID	OD	PSI	MPa					
H21006020	6.0	11.4	350	2.4	1450	72	0.115	20	45.56
H21006100	6.0	11.4	350	2.4	1450	72	0.115	100	227.82
H21008020	8.0	14.6	350	2.4	1450	96	0.155	20	57.87
H21008100	8.0	14.6	350	2.4	1450	96	0.155	100	289.34
H21010020	10.0	16.4	350	2.4	1450	120	0.180	20	63.79
H21010100	10.0	16.4	350	2.4	1450	120	0.180	100	318.96
H21012020	12.5	18.9	350	2.4	1450	150	0.215	20	79.74
H21012100	12.5	18.9	350	2.4	1450	150	0.215	100	398.69
H21020020	20.0	29.0	350	2.4	1450	240	0.470	20	141.25
H21020100	20.0	29.0	350	2.4	1450	240	0.470	100	706.26
H21025020	25.0	35.0	350	2.4	1450	300	0.645	20	216.43
H21025100	25.0	35.0	350	2.4	1450	300	0.645	100	1082.17
H21032020	32.0	43.0	350	2.4	1450	384	0.880	20	358.83
H21040020	40.0	50.4	300	2.0	1230	480	1.115	20	501.22
H21050020	50.0	63.5	250	1.7	1000	600	1.600	20	797.39

Price Group: HP

DA28

Superflex Yellow / Blue Hose Assembly



Application:	General purpose air & water supply with superior flexibility & toughness. Resistant to oil. UV stabilised.
Tube:	PVC (Poly Vinyl Chloride)
Reinforcing:	High strength polyester braid
Cover:	PVC (Poly Vinyl Chloride)
Temperature:	0°C to 60°C
Standards:	¼" to 1½" - Exceeds AS/NZS 2554:1998 Class B for burst pressure 2" - Exceeds AS/NZS 2554:1998 Class C for burst pressure
Construction:	Yellow ribbed cover with blue smooth stripe, black tube

Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius	Weight kg/mtr	Length (mtr)	Price \$ per coil
	ID	OD	PSI	MPa					
H21012020F	12.5	18.9	300	2.1	1200	150	0.215	20	103.32
H21025020F	25.0	35.0	300	2.1	1200	300	0.645	20	238.11
H21040020F	40.0	50.4	225	1.6	900	480	1.082	20	687.22

Price Group: HP

DA28

Complete hose data specification sheets are available upon request.

