

## CO<sup>2</sup> Fire Extinguisher

Carbon Dioxide (CO<sup>2</sup>) is used on class B (Flammable Liquid) fires.

CO<sup>2</sup> is safe to use on live electrical fires. CO<sup>2</sup> fire extinguishers are available in a variety of sizes with light weight steel cylinders.

All fire extinguishers are manufactured and approved to AS1841.5 and AS1841.1



### Technical Specifications

	2.0	3.5	5.0
Capacity (kg):	2.0	3.5	5.0
Fire Class:	BE	BE	BE
Fire Rating:	2B:E	5BE	5B:E
Operating Temperature:	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C
Test Pressure: *	22MPa (220BAR)	22MPa (220BAR)	22MPa (220BAR)
Operating Pressure At:	5.0 MPa (50 BAR)	5.0 MPa (50 BAR)	5.0 MPa (50 BAR)
Min Discharge Time:	14 secs	11 secs	15 secs
Cylinder Material:	Chromium Molybdenum, BS5045 Part 1	Chromium Molybdenum, BS5045 Part 1	Chromium Molybdenum, BS5045 Part 1
Operating Valve:	Forged Brass	Forged Brass	Forged Brass
Height:	625mm	595mm	770mm
Diameter:	105mm	138mm	138mm
Full Weight:	7.9kg	11.8kg	15.1kg
Carton Size (mm):	200x200x635	200x245x610	230x245x780

\* Test Pressure for Cylinder, Valve and Discharge Hose.


Size (kg)	Part No.	Price \$
2.0	EXT-CO2-2KG	366.44
3.5	EXT-CO2-3.5KG	456.92
5.0	EXT-CO2-5KG	480.75

Price Group: SD

FP04



Refer page 446 for Extinguisher Signs



Refer page 445 for Maintenance Record Tag