


Rubber Flange Gaskets - AS2129

NB (mm)	Table D		Table E	
	Part No.	Price \$	Part No.	Price \$
25	---	---	GAS-FF-25E	4.36
32	---	---	GAS-FF-32E	3.37
40	---	---	GAS-FF-40E	5.11
50	---	---	GAS-FF-50E	5.98
65	---	---	GAS-FF-65E	9.62
80	---	---	GAS-FF-80E	9.03
100	GAS-FF-100D	6.08	GAS-FF-100E	5.67
125	---	---	GAS-FF-125E	19.43
150	GAS-FF-150D	15.12	GAS-FF-150E	9.25
200	GAS-FF-200D	24.48	GAS-FF-200E	14.32
250	---	---	GAS-FF-250E	28.38
300	---	---	GAS-FF-300E	35.70



Price Group: SD
GA01

Non Asbestos Flange Gaskets (full face) AS2129

Application:	Air, water, gas and some chemicals. Contact Dixon™ for specific data.
Design:	An all purpose flange gasket manufactured from Aramid fibres bound with Nitrile Butadiene Rubber (NBR)
Pressure Rating:	Working Pressure 1600 PSI (11 MPa)
Temperature Rating:	Maximum 400°C
Standards:	Complies with ASTM F712230-M5 and DIN3535 parts 4 and 6

NB (mm)	Table D		Table E		Table H	
	Part No.	Price \$	Part No.	Price \$	Part No.	Price \$
50	---	---	GAS-NA-FF-50E	29.17	---	---
80	---	---	GAS-NA-FF-80E	37.29	---	---
100	GAS-NA-FF-100D	50.75	GAS-NA-FF-100E	28.14	---	---
150	---	---	GAS-NA-FF-150E	39.55	GAS-NA-FF-150H	76.92
200	---	---	GAS-NA-FF-200E	99.10	---	---

Price Group: SD
GA01

Neoprene Flange Gaskets (full face) AS2129

Application:	Fire-proof hydraulic liquids, lubricating oils, fuel oils, hydraulic oils, petrol (ULP), kerosene, water (under 80°C), alcohols, diluted acids, alkalies, gases, vegetable oils, animal fats, aliphatic hydrocarbons.
Design:	Black neoprene 3.2mm thick Flame, ozone and sunlight resistant

NB (mm)	Table E	
	Part No.	Price \$
50	GAS-NEO-FF-50E	12.37

Price Group: SD
GA02

Other flange tables and gaskets available on request - refer to page 643-645 for flange information.