


Brass Ball Valve Female x Female BSP - AGA Approved



Lever Handle



T Handle

Design:	Full bore, blow-proof stem
End Connection:	Female x Female BSP
Body Materials:	Nickel plated brass with stainless steel handle
Seat & Ball:	PTFE seat and chrome plated brass ball
Temperature:	-10°C to 110°C
Approvals:	AGA Certified
Application:	Recommended for general use with water, oil & gas

Lever Handle *

Size		Part No.	Working Pressure		Price \$
inch	mm		PSI	MPa	
¼	6	BBVAGA006	600	4.1	16.77
¾	10	BBVAGA010	600	4.1	17.85
½	15	BBVAGA012	600	4.1	18.75
¾	20	BBVAGA020	600	4.1	27.49
1	25	BBVAGA025	600	4.1	41.02
1¼	32	BBVAGA032	600	4.1	76.08
1½	40	BBVAGA040	600	4.1	108.70
2	50	BBVAGA050	600	4.1	150.61

* Superseded model will be supplied whilst stocks last - check with Dixon™ at time of order.

Price Group: SD
AR01

Size		Part No.	Working Pressure		Price \$
inch	mm		PSI	MPa	
¼	6	BBVAGAT006	710	4.9	18.47
¾	10	BBVAGAT010	710	4.9	18.41
½	15	BBVAGAT012	710	4.9	23.03
¾	20	BBVAGAT020	570	3.9	33.79
1	25	BBVAGAT025	570	3.9	49.18

Price Group: SD
AR01

Brass Ball Valve Screwed Male / Female BSP - AGA Approved



M



Design:	Full Bore
End Connection:	Screwed Male/Female BSP.
Body Materials:	Brass
Seat & Trim:	PTFE Seats
Temperature:	-20°C, 60°C (class T2 under EN331)
Application:	Industrial pneumatic and hydraulic applications. Water, oil & gas.

Size		Part No.	Working Pressure		Price \$
inch	mm		PSI	MPa	
½	15	BBVAGAMF012	710	4.9	26.04
¾	20	BBVAGAMF020	570	3.9	35.80
1	25	BBVAGAMF025	570	3.9	54.24
1½	40	BRBLMF040	363	2.5	119.34

Price Group: SD
AR01