


## Mini Ball Valves

<b>Design:</b>	Blow-out proof stem with chrome ball
<b>End Connection:</b>	Screwed Female & Male/ Female BSP ISO228 (equivalent to DIN259 and BS2779)
<b>Body Materials:</b>	Nickel-plated brass
<b>Seat &amp; Trim:</b>	PTFE Seats
<b>Temperature:</b>	-0°C - 90°C. Rated to 220 PSI
<b>Application:</b>	Domestic water services, heating and air-conditioning plants, compressed air systems


### Female BSP x Female BSP

Size		Part No.	Working Pressure		Price \$
inch	mm		PSI	MPa	
¼	6	MBVFF006	220	1.5	12.05
⅜	10	MBVFF010	220	1.5	11.56
½	15	MBVFF012	220	1.5	14.58
¾	20	MBVFF020	220	1.5	22.47

Price Group: SD  
AR01



art. 125



art. 126

### Female BSP x Male BSP

Size		Part No.	Working Pressure		Price \$
inch	mm		PSI	MPa	
¼	6	MBVMF006	220	1.5	10.97
⅜	10	MBVMF010	220	1.5	10.61
½	15	MBVMF012	220	1.5	13.41
¾	20	MBVMF020	220	1.5	22.55


Price Group: SD  
AR01

## Lockable Ball Valves

<b>Design:</b>	Lever operated, C/W Locking device, for lock open or lock closed.
<b>End Connection:</b>	Screwed Female BSP
<b>Body Materials:</b>	Brass, Nickel Plated
<b>Seat &amp; Trim:</b>	PTFE seats
<b>Temperature:</b>	-10 to 110°C
<b>Application:</b>	For Industrial Pneumatic and Hydraulic applications. Water, oil & gas
<b>Approvals:</b>	AGA and Watermark

Size		Part No.	Price \$
inch	mm		
½	15	V15LO	20.61
¾	20	V20LO	26.54
1	25	V25LO	46.45
1¼	32	V32LO	75.83
1½	40	V40LO	114.56
2	50	V50LO	180.22

Price Group: FE  
VB06



M