


"Deadman" Stainless Steel Spring Return Handle Ball Valve




Design:	Deadman spring return ball valve
End Connection:	Screwed BSP female ends
Body Materials:	SS 316
Seat & Trim:	PTFE Seats and CF8M (SS 316)
Options:	2 piece 1000 PSI BSP or 2 piece 2000 PSI NPT available or request
Application:	Mainly used as a fail-safe closed valve for petro chemical and other media where spillage can cause damage, injury or loss if an operator incorrectly opens the valve

Female BSP x Female BSP					
Size		Part No.	Weight (kg)	WP WOG PSI	Price \$
inch	mm				
½	15	SAS22015	1.2	1000	319.38
¾	20	SAS22020	1.4	1000	386.88
1	25	SAS22025	1.8	1000	464.46
1½	40	SAS22040	2.8	1000	773.76
2	50	SAS22050	3.9	1000	958.13

Price Group: SD
AR02

ANSI Ball Valve - Petro-Chemical - Fire Safe Certified




316 stainless steel

Applications:	Petroleum, Oil & Gas, Low pressure saturated steam, Mining & Industrial applications
Design:	Fire Safe Certified Ball Vaves Flanged ANSI 150 to API607
End Connection:	Flanged & Drilled ANSI 150
Body Materials:	Cast Steel (ASTM A216 WCB) & Stainless Steel (CF8M -SS316)
Seat & Trim:	Ball - ASTM A351 CF8M, Seat - R-PTFE
Pressure:	285 PSI for Ware, Oil, Gas & Some Corrosive Fluids
Options:	ANSI Class 300 & 600 in WCB & CF8M available on request
Accessories:	Gear operated, electric & pneumatic actuated
Features:	Fire Safe Certified with Lockable Levers , 3.1 Test Certificates available on request

API 607 Fire SAFE Certified ANSI 150 Ball Valves					
Size NB		316SS (CF8M) Part No.	Price \$	Cast Steel (WCB) Part No.	Price \$
inch	mm				
½	15	V2FH-015	420.40	V2FH-WCB-015	294.51
¾	20	V2FH-020	512.02	V2FH-WCB-020	343.60
1	25	V2FH-025	619.82	V2FH-WCB-025	431.96
1¼	32	V2FH-032	780.00	V2FH-WCB-032	451.58
1½	40	V2FH-040	975.54	V2FH-WCB-040	549.75
2	50	V2FH-050	1333.91	V2FH-WCB-050	746.09
2½	65	V2FH-065	2328.37	V2FH-WCB-065	1050.43
3	80	V2FH-080	2667.83	V2FH-WCB-080	1310.58
4	100	V2FH-100	4107.06	V2FH-WCB-100	2076.32
6	150	V2FH-150	10055.22	V2FH-WCB-150	4368.60


Price Group: SD
VS01

Available on request
- Ansi Class 300 in 316SS
- Ansi Class 150 in Ansi 300 in cast steel



cast steel

ANSI 150 & Table E Ball Valves



Design:	SS Ball Valve flanged ANSI 150 lever operated
End Connection:	Flanged & drilled to ANSI 150LB / un-drilled / Table D/E
Body Materials:	CF8M (SS316), SS ball
Seat & Trim:	PTFE seat
Pressure:	ANSI 150 is 285PSI for water, oil & gas & corrosive fluids
Accessories:	Gear operated, electric & pneumatic actuated

Size NB		ANSI 150 Drilled		Drilled Table D/E	
inch	mm	Part No.	Price \$	Part No.	Price \$
½	15	V2F-150-015	269.49	---	---
¾	20	V2F-150-020	285.65	---	---
1	25	V2F-150-025	329.31	---	---
1¼	32	V2F-150-032	560.53	---	---
1½	40	V2F-150-040	646.76	---	---
2	50	V2F-150-050	854.16	V2F-150DR-050	970.16
2½	65	V2F-150-065	1390.54	V2F-150DR-065	1509.12
3	80	V2F-150-080	1537.73	V2F-150DR-080	1832.51
4	100	V2F-150-100	2356.91	V2F-150DR-100	2200.81
6	150	V2F-150-150	5184.93	V2F-150DR-150	5497.52
8	200	V2F-150-200	12396.38	---	---

Available on request
- Table E drilled valves ½" to 6"

Price Group: SD
VS01

